

Recommended Rope Requirements Per Boat (updated 7/08/23)

| Rope Description | Rope Type | Colour | Diameter | Quantity | Length (m) |
|---|-----------------------------|--------|----------|----------|------------|
| Main Sheet | Polyester Double Braid | Blue | 6mm | 1 | 8 |
| Jib Sheet | Polyester Double Braid | Red | 6mm | 1 | 7 |
| Screecher Sheet | Polyester Double Braid | Green | 8mm | 1 | 11.5 |
| Tapered Main Halyard (0.8m Tapered To Core For Halyard Lock) | Dyneema Core Polyester | Blue | 5mm | 1 | 12 |
| Jib Halyard | Dyneema Core Polyester | Red | 4mm | 1 | 8.5 |
| Screecher Halyard | Dyneema Core Polyester | Green | 4mm | 1 | 10 |
| Screecher Furler Line | Marlow Excel Control Line | Green | 5mm | 1 | 9.5 |
| Screecher Block Ties | Dyneema Core Polyester | Black | 3mm | 2 | 0.8 |
| Forestay Tie | Dyneema Core Polyester | Black | 3mm | 1 | 1.2 |
| Cunningham | Dyneema Core Polyester | Blue | 4mm | 1 | 2.5 |
| Main Block Line to Deck | Dyneema Core Polyester | Black | 3mm | 1 | 0.8 |
| Centerboard Handle | Polyester Double Braid | Any | 6mm | 1 | 0.6 |
| Trampolines Inboard Tie | Dyneema Core Polyester | Blue | 4mm | 2 | 2.5 |
| Trampolines Outboard Tie Across | Dyneema Core Polyester | Any | 4mm | 2 | 3 |
| Trampolines Outboard Tie Along | Dyneema Core Polyester | Any | 4mm | 2 | 2.5 |
| Trailer Sides | Polyester Double Braid | Any | 6mm | 2 | 2.2 |
| Trailer Front Tie | Dyneema Core Polyester | Any | 4mm | 1 | 1 |
| Forestay Ring Tie | Dyneema | | 8mm | 1 | 0.8 |
| Stay Lengths | | | | | |
| Forestay | 1 x 19 G316 | Wire | 2.5mm | 1 | 4.7 |
| Sidestay | 1 x 19 G316 | Wire | 2.5mm | 2 | 4.9 |
| Self Tacker | | | | | |
| Bow Tie For Block | Dyneema | | 2mm | 1 | 0.7 |
| Deck Sheet Block To Shackle | Dyneema | | 3mm | 1 | 2.1 |
| Car Control | Polyester Case Dyneema Core | red | 3mm | 1 | 2.1 |